

Common network ports

Typical destination ports and transports used in everyday administration.

Core network services

- 22 TCP** - SSH; also SFTP over SSH.
- 53 UDP/TCP** - DNS; TCP is also used for normal DNS queries when needed.
- 67/68 UDP** - DHCPv4 server/client.
- 80 TCP** - HTTP.
- 123 UDP** - NTP time service.
- 161 UDP** - common SNMP queries.
- 162 UDP** - common SNMP traps.
- 443 TCP** - HTTPS over TCP.
- 443 UDP** - commonly HTTP/3 over QUIC.

Mail services

- 25 TCP** - SMTP transport / server relay.
 - 465 TCP** - submission with implicit TLS.
 - 587 TCP** - message submission, commonly with STARTTLS.
 - 143 / 993 TCP** - IMAP / IMAP over implicit TLS.
 - 110 / 995 TCP** - POP3 / POP3 over implicit TLS.
- Port 25 is not interchangeable with authenticated client submission.

Web and file access

- 445 TCP** - SMB.
 - 3389 TCP/UDP** - RDP.
 - 2049 TCP** - commonly NFSv4; other NFS versions and setups can need additional ports.
- A service can be configured to use a different port.

Active Directory-related services

- 88 TCP/UDP** - Kerberos.
 - 389 TCP/UDP** - LDAP / CLDAP.
 - 636 TCP** - LDAP over TLS.
 - 3268 / 3269 TCP** - Global Catalog / TLS.
 - 135 TCP** - RPC endpoint mapper.
 - 49152-65535 TCP** - default modern Windows dynamic RPC server range; configuration and workload matter.
- AD also relies on DNS, time and SMB. This is not a complete firewall rule set.

Management and databases

- 5985 / 5986 TCP** - WinRM HTTP / HTTPS.
- 1433 TCP** - common SQL Server listener.
- 3306 TCP** - MySQL / MariaDB.
- 5432 TCP** - PostgreSQL.
- 514 UDP / 6514 TCP** - syslog / syslog over TLS.

Test the correct transport

Test-NetConnection host.example -Port 443

Windows TCP check. Replace the target with your host.

ss -lntup

Linux local listeners; process details can require privileges.

A TCP test cannot prove that a UDP service works. For DNS, make a DNS query. For HTTPS, also test the TLS connection and application response.

Before changing a firewall

Confirm source, destination, traffic direction, transport, destination port and actual listener. Limit access to the intended systems. An open port does not prove a service is healthy or encrypted; a timeout alone does not identify which device dropped the traffic.